



DENON PMA-1700NE

PMA-1700NE âm thanh trong trẻo, rõ nét, chi tiết và chính xác hơn

Thông số

General		
Unit (W x H x D mm)	434 x 135 x 410	
Net weight	17.6kg	
Heatsink for Power Amplifier	Extruded Aluminum	
Specifications		
Audio	Rated Output Power	70W + 70W (8ohm, 20Hz-20kHz, THD0.07%) 140W + 140W (4ohm, 1kHz, THD0.7%)
	Total Harmonic distortion	0.01 % (Rated output: -3 dB), 8 ohm/ohms, 1 kHz*
	Input Sensitivity: Phono input	MM: 2.5 mV / 47 kohm MC: 200 μV / 100 ohm
	Input Sensitivity: CD/LINE/RECORDER	125 mV / 19 kohm
	Input Sensitivity: Power Amp input	0.85V / 47kohm (EXT. PRE)
	Signal to Noise Ratio	PHONO (MM): (89dB) PHONO (MC): (74dB) CD: (107dB)
Power Consump.	Power Consumption	295W
	at Standby	0.2W TV autoplay off 0.4W TV autoplay on
Digital Audio	DAC Circuit	PCM1795
	Digital Processing	Advanced AL32 Processing Plus
	DAC Master Clock Design	Yes
	Asynchronous mode (for USB-B input)	Yes

Connectivity		
Audio Video	Phono Input	Yes (MM / MC) *default=MM
	Analog Input (include Phono) / REC Out (RCA)	4/1 (PHONO / CD / NETWORK, AUX/ RECORDER)
	Optical input / output (Maximum Support)	2 / 0 (192kHz/24bit)
	Coaxial input / output (Maximum Support)	1 / 0 (192kHz/24bit)
	Speaker Terminal	Gold Plated
	Headphone Output	1 (Turn off the speaker when inserting headphone)*
Control /other	Remote Control -> RC-1249 Remote Control Bus Terminal	Yes
	Network	Wi-Fi HEOS
USB B	USB B (USB DAC)	No
	PCM Sample Rate	No
	DSD Audio Streaming (DoP)	1 (Rear) ~384kHz/32bit ~11.2MHz
Audio Feature		
Analog Audio	Power Amplifier Circuit	New UHC-MOS Single Push Pull (7)
	Pre Amplifier Circuit	Variable Gain Preamp (OP AMP)
	Bass/Treble/Mid/Balance Control	Yes / Yes / - / Yes
	Source Direct	Yes
	Analog Amp Mode	Yes (button on front panel)