



E-5000

Ampli tích hợp E-5000 trình diễn những giai điệu của bản nhạc một cách tinh tế đến từng chi tiết.

Technical Information

E-5000 Guaranteed Specifications [Guaranteed specifications are measured according to EIA standard RS-490]

Rated Continuous Average Output (20 – 20,000 Hz)	both channels driven	4-ohm load	320 W / ch
		8-ohm load	240 W / ch
Total Harmonic Distortion (20 – 20,000 Hz)	both channels driven	4 to 16 ohm load	0.05%
Intermodulation Distortion			0.01%
Frequency Response	INPUT (BALANCED / LINE)	*	20 – 20,000 Hz (0, -0.5 dB)
	MAIN IN (BALANCED / LINE)	*	20 – 20,000 Hz (0, -0.2 dB)
	At 1 W output		3 – 150,000 Hz (0, -3.0 dB)
Damping Factor	with 8-ohm load, 50 Hz		1,000
Input Sensitivity	At rated output	INPUT (BALANCED / LINE)	220 mV
		MAIN IN (BALANCED / LINE)	1.74 V
	EIA (at 1 W output)	INPUT (BALANCED / LINE)	14.2 mV
		MAIN IN (BALANCED / LINE)	113 mV
Input Impedance		INPUT (BALANCED)	40 kilohms
		INPUT (LINE)	20 kilohms
		MAIN IN (BALANCED)	40 kilohms
		MAIN IN (LINE)	20 kilohms
Maximum Input Voltage	INPUT (BALANCED / LINE)		5.0 V
Output Voltage and Impedance	At rated continuous average output	PRE OUTPUT (BALANCED / LINE)	1.74 V
			50 ohms
Gain	INPUT (BALANCED / LINE) → PRE OUTPUT (BALANCED / LINE)		18 dB
	MAIN IN (BALANCED / LINE) → SPEAKER OUTPUT		28 dB

*: At rated continuous average output

Supplied accessories

- AC power cord

- Remote Commander RC-250

Tone Controls	Turnover frequency and adjustment range	Bass: 300 Hz	±10 dB
		Treble: 3 kHz	±10 dB
Loudness Compensator			+6 dB (100 Hz)
Attenuator			-20 dB
S/N Ratio	At rated output (input shorted, A weighting)	INPUT (BALANCED / LINE)	111 dB
		MAIN IN (BALANCED / LINE)	126 dB
	EIA	INPUT (BALANCED / LINE)	97 dB
		MAIN IN (BALANCED / LINE)	101 dB
Output Meters		Logarithmic compression peak level display showing output in dB / %	
Output Load Impedance	Speaker set 1		4 – 16 ohms
	Speaker set 2		8 – 16 ohms
Stereo Headphones	Compatible impedance		8 ohms or higher
Power requirements	120 V, 220 V, 230 V AC (voltage as indicated on rear panel)		50 / 60 Hz
Power Consumption	Idle		98 W
	In accordance with IEC 60065		570 W
	Stand-by		0.3 W
Maximum dimensions	Width 465 mm (18.31") × Height 211 mm (8.31") × Depth 502 mm (19.76")		
Mass	Net		33.8 kg (74.5 lbs)
	In shipping carton		43 kg (95 lbs)