ROKSAN







ATTESSA-STREAM-ATTST

Ampli tích hợp Streamer Roksan Attessa là bước tiến theo xu hướng mới của việc nghe nhạc ngày nay

Technical Information

Power Output into 8 Ohm Power Output into 4 Ohm

THD+N

Amplifier Type Gain

Channel Separation Frequency Response

Pre-Amplifier*

Volume Channel Matching THD+N

Channel Separation

Signal to Noise Ratio

BluOS

(Streaming Amp ONLY)

Audio Formats

Hi-Resolution Audio Formats

80 Wrms per Channel, Both Channels Driven, Nominal (THD+N <1 %) 130 Wrms per Channel, Both Channels Driven, Nominal (THD+N <1 %)

<0.02 % (1 kHz, 2 channels, 1 W @ 8 Ohms, A-Weighted)

Class AB

29 dB

<0.5 dB

>80 dBa 1 W/ 8 R, >98 dBa 75 W/ 8 R

>75 dB @10 kHz 5 Hz to 50 kHz (-3 dB)

<0.25 dB

0.002 % (1 kHz. 2 Vrms, A-Weighted)

>102 dB (1 kHz, 100 mV) >104 dB (unweighted)

 $47 \text{ k}\Omega$ / 56 pf loading; gain settings suitable for 12 mV, 6 mV, 3 mV output cartridges

MP3, AAC, WMA, OGG, WMA-L, ALAC, OPUS

MOA, FLAC, WAV, AIFF, Supports converted DSD playback via the BluOS desktop app (only)

Sampling Rate Up to 32 bit / 192 kHz

Supported Operating Systems. Plays music from network shares on the following desktop operating

Microsoft Windows XP, 2000, Vista, 7, 8 to current Windows

Operating Systems and Mac OS X versions

Mobile Device Support BluOS App - free on Android & iOS, available within Google Play & Apple App Store Mobile Device Control BluOS application can control inputs, volume and configure BluOS related settings Supported Cloud Services Amazon Alexa, Amazon Music, Spotify, TIDAL, Deezer, Oobuz, HDTracks,

HighResAudio, Murfie, JUKE, Napster, Slacker Radio, KKBox, Bugs

Free Internet Radio TuneIn Radio, iHeartRadio, Calm Radio, Radio Paradise

Control Integrations Crestron, Control4 (OS 3), Control4 (2.9.1), RTI, URC, Push, Lutron, ELAN, iPort

Digital Inputs

up to 24 bit/ 192 kHz PCM Digital Coax Input Digital Optical Input up to 24 bit/ 96 kHz PCM

DAC

Format Support

up to 192 kHz/ 24 bit Sampling Rate

Signal to Noise Ratio

IR Receiver 5V - 14V, mono 3.5mm jack plug, any polarity

12V Trigger Input 5V-14V, 3.5mm jack dual polarity 12v Trigger Output 3.5mm jack Pass through from input only

Construction Formed plated steel and bespoke machine anodised aluminium front panel

Dimensions (H x W x D) 76 x 432 x 373 mm (Inc Feet, Connectors & Buttons) 3 x 17 x 1411/16 Inches

106 dB (A-Weighted)

Streaming Amplifier Weight 10.48 Kg 23 lb Integrated Amplifier Weight 10.37 Kg 22 lb 14 oz

Mains input 100-130 VAC 50/60 Hz (Auto Selecting) 210-240 VAC 50/60 Hz

(Operational down to 85 VAC with reduced outputpower)

Power consumption Full Power: 400 W max Standby: <0.5 W Network Standby: 6 W

Bluetooth: A2DP Audio profile Bluetooth Codecs: SBC, aptX & AAC

Bluetooth Range: 15 m (typical, clear line of sight)