



## SILVER300NWALNUT(7G)

The Silver 300 7G features real-wood veneers for a natural look, along with a newly developed Rigid Surface Technology

### Technical Information

System Format	3 - way
Nominal Impedance	8 Ohms
Power Handling (RMS)	200 W
Port Tuning Frequency	40 Hz
Frequency Response, In-Room (-6dB)	31 Hz - 35 kHz
Minimum Impedance	4.0 Ohms @ 160 Hz
Recommended Amplifier Requirements	80 - 200 W
Bass Alignment	Bass reflex
	Dual HiVe II port system
Sensitivity (2.83v @ 1m)	87.5 dB
Maximum SPL (single, free-field)	110 dB
Crossover Frequency	L.F: 750 Hz
	M.F/ H.F: 2.8 kHz
Drive Unit Complement	2 x 6" C-CAM RST II bass driver
	1 x 3" C-CAM RST II mid-range driver
	1 x 1" (25 mm) C-CAM Gold Dome tweeter with UD Waveguide II
External Dimensions (Including Grille and Terminals (H x W x D))	1000 x 185 x 332 mm
External Dimensions (including Outtrigger Feet and Spikes (H x W x D))	1045 x 274 x 389 mm
Weight (each)	19.3 kg (42 lb 9 oz)
Sold As	Pair