



SILVERW12HGB

The Silver W-12 6G provides the perfect complement to your speaker set-up, making any song seem fuller, deeper and more impressive

Technical Information

Lower Frequency Limit	20 Hz (Typical IEC room)
Amplifier Output	500 W continuous
Phase Control	0 & 180 degrees
Drive Unit Complement	1 x 12" C-CAM subwoofer driver featuring triple suspension and 3" long throw voice coil
Upper Frequency Limit	40 – 120 Hz variable
Amplifier Classification	Class-D amplifier with switched-mode power supply (SMPSU)
Auto Sensing	Line Level >2 mV
Trigger Input	5 – 12 V via 3.5 mm mono mini-jack socket
Mains Input Voltage	110 – 120 Vac / 220 – 240 Vac 50/60 Hz (Electronically Auto selected)
Low Pass Filter Alignment	Active 4th order 24 db/octave 1: Movie 2: Music 3: Impact
Input Level Requirements	Standby after 20 minutes if no signal sensed
Cabinet Dimensions (Excluding Grille and Terminals (H x W x D))	340 x 340 x 380 mm
Dimensions (Including Grille, Amp and Feet)	370 x 340 x 410 mm
Power Consumption	400 W / 0.5 W in Standby (ErP approved)
Sold As	Single Unit