



X50PRO-SR

X50Pro là Music Server kỹ thuật số thuần túy thuộc dòng tham chiếu để cung cấp âm thanh và các chức năng tuyệt vời.

Technical Information

Model name	cocktailAudio X50Pro		TUNER	DAB+/FM	DAB+/FM Tuner built-in(Selectable for DAB/DAB+ or FM Radio)
Host CPU & Memory	CPU: Quad Core ARM Cortex A9 running at 1.0GHz		Connectivity	USB Host	USB3.0(5V/1A) x 2 at rear
Main Memory	DDR-1066 1GByte			USB2.0(5V/1A) x 1 at front	
NAND Flash	8GByte		Network Wired	Giga Fast Ethernet(10/100/1000Mbps)	
CD Player	Type	Front Loading	Wireless(Optional)	802.11b/g/n WiFi USB dongle(Optional)	
Supported media	CD, CD-DA, CD-R, CD-RW, DVD-R/RW		12V Trigger	Out	Max 200mA, 12V
Display	7.0" TFT LCD(1,024 x 600pixels)(* able to connect to ext. screen via HDMI out)		In	Max 12V	
Interface	Key & Jog(Volume/Scroll), IR Remote Control, Customized Remote App for iOS		HDMI Out	Connect to external screen(* Shared with HDMI Audio Out)	
Android devices, Web Interface			Codec & Format	supported	
Digital Output	(Variable/Fixed)	COAXIAL x 1 S/PDIF 75ohm RCA, Sample rate: up to 24bit/192Khz		MQA, DSD(DSD64, DSD128, DSD256), DXD(24bit/352.8Khz), PCM 32bit/384Khz,	
TOSLINK x 1	S/PDIF, Sample rate: up to 24bit/192Khz			HD WAV(24bit/192KHz), HD FLAC(24bit/192KHz), APE/CUE, WAV, FLAC, ALAC, AIFF, AIF, AAC, M4A, MP3, WMA, Ogg Vorbis.	
AES/EBU/XRL x 1	1110ohm, Sample rate: up to 24bit/192Khz		Network Protocols	Supported	
IPS Out x 3	RJ45 Native DSD, DoP, PCM up to 24bit/192Khz			UPnP(DLNA) Server/Client/Media Renderer, Samba Server/Client, FTP Server, Web Server, etc	
HDMI#1 Native DSD, DoP, PCM up to 24bit/192Khz			Internet	Services Internet Radio	
HDMI#2 Native DSD, DoP, PCM up to 24bit/192Khz				Airable	
USB Audio x 1	USB Audio Class 2.0 Out(supports up to Native DSD256)		Online Music Services	TIDAL, Deezer, Qobuz, Napster, Spotify Connect, HighResAudio	
HDMI Out x 1	HDMI Audio Out(*Shared with HDMI Out for external screen)		Supported OSD languages	English, German, French, Spanish, Italian, Polish, Dutch, Russian, Traditional Chinese, Japanese, Korean,	
Word Clock out	up to 192Khz		Power Source	AC110 - 240V / 50 - 60Hz Free Voltage	
Digital Input	COAXIAL x 1 Sample Rate up to 24bit/192Khz		Enclosure	Material Whole enclosure is fabricated by precision CNC machine with beautiful glasssanding high-quality aluminum	
TOSLINK x 1	Sample Rate up to 24bit/192Khz		Dimension	Without foot 440mm(W) x 329mm(D) x 118mm(H)	
Supported Storage	Hard Disk 2.5" SATA, up to 8TB * Two(2) Storage Decks		With foot	440mm(W) x 329mm(D) x 130mm(H)	
* RAID System for two storages			Weight	11.5Kg (Device only without accessory and carton box)	
(3 modes: Mirror, Stripe or Big)			Certificate	CE, FCC, EMI, etc	
3.5" SATA, up to 8TB					
SSD 2.5" SATA, up to 8TB					